STATE OF NORTH CAROLINA, DEPARTMENT OF ADMINISTRATION			
DIVISION OF PURCHASE AND CONTRACT			
	116 West Jones Street, Raleigh, NC 27603-8002		
Term Contract	765K	10' and 12' Truck Mounted Hydraulic Snow Plows	
Effective Dates	June 19, 2	011 through June 18, 2014	
Bid Number	201100729	9	
Administrator	Mike Brend	dle	
Phone	(919) 807-	4516	
Fax	(919) 807-	4510	
E-Mail	Tmike.brei	ndle@doa.nc.gov	
Last Updated	June 19, 2	011	

1. General Information

This contract describes a 10 Ft. and 12 Ft., Truck Front Mounted, Hydraulic Powered, Reversible, and Hydraulic Angling, moldboard type Snow Plow. The unit offered shall be new, unused and a current model under standard production by the manufacturer.

2. Scope of Contract

The scope of this contract is intended to cover the State's normal requirements for the above mentioned equipment for use by all State Agencies, Institutions, and all Public Schools except those exempt by Statute noted herein. As per House Bill 490, Community Colleges have the flexibility to not use this contract if they can locate the item(s) that is the same or substantially similar in quality, service, and performance as items available under State term contracts and the delivered price is less than that on term contract with all features, terms, and conditions being the same. Contract period shall be from date of an award and continuing for a period of three (3) years subject to the continuation of the program and the availability of funds.

3. Taxes

Prices or Discounts shown herein do not include any North Carolina sales or use taxes.

4. Abnormal Quantities

With the exception of NCDOT, any agency requirement that exceeds 10 units must be forwarded to the Division of Purchase and Contract for processing. The Division, at its sole discretion, may process any such requirement in one of the following ways:

- 1. Purchase may be authorized at the current level of pricing with the current contract vendor(s)
- 2. Additional discounts from the current level of pricing may be negotiated with the current contract vendor(s)
- 3. A separate Invitation for Bids may be issued for the requirement

5. Minimum Orders

This contract will be for a minimum order of 1 unit for any single order.

6. Placement of Orders

Orders will be placed throughout the contract period on an as-needed basis for the quantity required at the time, and will be issued directly to the respective contractor(s) or their designated suppliers. Contract changes, if any, over the life of the contract are implemented by contract addenda released by the Contract Administrator to the contractor. If the contractor is accepting orders and/or delivering through other parties, for example a manufacturer accepting orders and delivering through a dealer network or dealers receiving orders through a network of other dealers, then it is the responsibility of the contractor to apprise such parties of all such contract addenda.

7. Delivery

The contractor(s) will complete delivery within 120 days ARO.

In the event the delivery is not received within the contract delivery period, the contractor may be held in default in accordance with paragraph 1, DEFAULT AND PERFORMANCE BOND in the North Carolina General Contract Terms and Conditions, and the state may procure the articles or services from other sources and hold the contractor responsible for excess cost occasioned thereby.

8. Transportation Charges

All goods shall be delivered FOB DESTINATION when the "order value" is 1 unit or more, when shipped to a single destination.

<u>Note!</u> All shipments should be inspected for damage immediately upon receipt.

9. Item Pricing Information

GROUP 2-NON-NCDOT: PRICING TO INCLUDE INSTALLATION BY THE ORDERING AGENCY

Item	Description	UNIT PRICE
4	Moldboard type snow plow, 10 foot, hydraulic Powered, and reversible.	\$ 3961.50
		\$ 3701.30
		Optional pricing:
		1)Add \$ 195.00 for vendor to install
		at vendor location
		2)Add \$ 1740for vendor to install at
		ordering agency location
5	Moldboard type snow plow, 12 foot,	
	hydraulic Powered, and reversible.	\$ 4134.40
		¥ 113 1.10
		Optional pricing:
		1)Add \$ 195.00 for vendor to install
		at vendor location
		2)Add \$ 1740.00 for vendor to
		install at ordering agency location
6	Same as item 2,Moldboard type snow	
	plow, 12 foot, hydraulic Powered, and	\$ 4088.80
	reversible, except plow must have a 30 inches height (Low Profile)	\$ 4088.80
		Optional pricing:
		1)Add \$ 195.00 for vendor to install
		at vendor location
		2)Add \$ 1740.00 for vendor to
		install at ordering agency location

10. Price Lists and Catalogs

The successful contractor must furnish descriptive literature to any agency within seven (7) consecutive days after request of the agency. Failure to comply with these requirements may subject the contractor to removal from the contract.

11. Contractors

All known minority, women and disabled owned businesses, as well as disabled business enterprises and nonprofit work centers for the blind and severely disabled, including dealers, will be identified with "Minority owned" "Woman owned", "Disabled Owned", "DBE" or "BSD" as appropriate after the vendor number. This is being done in an effort to recognize these businesses and to encourage and promote their use to the greatest extent permitted by law.

When more than one supplier is listed for a particular item, selection should be made, whenever possible, from any of the groups identified above, consistent with agency needs and price considerations.

Contractor Name	Address / Federal ID	City, State, Zip	Contact, Phone, Fax
GODWIN MFG.	17665 US HWY 421 S.	DUNN, NC 28335	JAMES GODWIN, JR.
			800.892.0181
			910.892.7402 FAX
			JRGODWIN@GODWINMFG.COM
	CALL VENDOR FOR		
	FEDERAL ID NUMBER		

12. Warranty

The contractor guarantees items offered to be free from any and all defects in material, packaging, and workmanship and agrees to replace defective items promptly at no charge to the State, for a period of time as stated in the mfr. warranty statement.

13. Substitutions

Substitutions are not permitted without prior approval of the Division of Purchase and Contract. Failure of the contractor to comply with this requirement may result in the removal of the contractor from the contract.

14. Additional information:

10 FT. & 12 FT. SNOW PLOWS, MODLBOARD TYPE, FRONT MOUNT TRUCK

GENERAL:

This specification describes a 10 Ft. and 12 Ft. truck front mounted hydraulic powered, reversible, and hydraulic angling, moldboard type snow plow Shall be complete with moldboard, fully enclosed dual tripping device (ram type, trip springs on back of moldboard not acceptable), hitch, rubber belting attached to top of moldboard for snow deflector, reflective markings on street side and curbside ends of moldboard, guide markers and. All quick disconnect shall confirm to ISO 7241-1 Series "B" (3/8 inch for up and down and 1/2 inch for right and left).

NOTE: ORDERING AGENCIES ARE STRONGLY ENCOURAGED TO CONFIRM SPECIFICATIONS AND THAT THESE SNOW PLOWS ARE COMPATIBLE AND WORKABLE AS DESIGNED ON YOUR TRUCK, WITH THE VENDOR PRIOR TO ORDERING ANY SNOW PLOWS

a.	Make: 10 Ft. GOOD ROADS	
	12 Ft. GOOD ROADS	

b.	Model: 10 Ft. 120M-10 12 Ft. 120M-12	
c.	Operating Weight: 10 Ft. 2000 LBS 12 Ft. 2100 LBS	
d.	BLANK	
e.	Vendor shall be certain that the 10 Ft. and the 12 Ft. plows must have all the necessary hardware for a complete mounting to the truck hydraulic system.	
f.	If required by the state, the successful bidder shall assist in the proper mounting at each location of assignment and a complete set of mounting instructions (including drawings) shall be furnished with each unit.	
g.	All components, hoses, cylinders and necessary hardware for each unit should be packed separately. (Necessary hardware and components for all units packed in one container is not acceptable).	
h.	Hydraulic cylinders must be including functional design which shall include snow plow hydraulic raise, lower, hold and angle features.	

MOLDBOARD:

a.	The moldboard assembly for both 10 foot and 12 foot plow, exclusive of a snow deflector, must have a minimum vertical height of 36 inches. Low profile 12 foot plows (under furnish & deliver) must have a 30 inches height.	
b.	Actual length of the moldboard for the 10-foot plow must be 120 inches and for the 12-foot plow 144 inches.	
c.	Shall have a minimum clearing path of 103 inches for the 10-foot plow and a minimum clearing path of 120 inches for the 12-foot plow when both plows are in a 30-degree angle.	
d.	Moldboard shall be single piece minimum 3/16-inch high tensile steel-formed 15-inch radius.	
e.	The cutting edge backup angle shall be 3x4x1/2" inch angle.	
f.	There shall be minimum of two- (2) 1/4x1-1/2" horizontal ribs and a minimum of eight (8) 1/2-x 3" inch vertical ribs.	
g.	Shall have a minimum 30-degree angle left and right.	
h.	Curb bumpers or guards shall be provided on both ends of the moldboard. Caster wheel or wear shoes are not required.	
i.	Shall have alternating red and white reflective marking (minimum 2 inches wide) on each end of the moldboard, beginning at the top of the cutting edge and continuing to the top of the moldboard.	

$\underline{\textbf{MOLDBOARD PUSH FRAME ASSEMBLY}};$

a.	The push frame shall attach to the moldboard in a manner to provide	
	ample road clearance of the assembly and permit sufficient oscillation for	
	the snow plow to follow road contour for even snow removal.	
b.	Shall have semi-circle and bracing of sufficient strength and rigidity to	
	assure structural integrity under severe use conditions	
c.	The "A" frame shall be of sufficient length to prevent moldboard, at full	
	angle position, coming into contact with any part of the vehicle.	
d.	The "A" Frame must have a 21 inch center to center hook-up dimension to	
	accept two (2) 1-1/4 inch pins	

SNOW DEFLECTOR:

a. A rubber belting type snow deflector shall be provided for the full length of the top of the moldboard

TRIPPING DEVICE:

a. Must have a fully enclosed dual trip spring assembly, lubricated type, which automatically returns the plow to the normal plowing position.

MOUNTING (HITCH):.

a.	Mounting hitch shall be bumper to axle type with 3x10 inch double acting	
	lift cylinder, with 21 inch center to center hook up.	
b.	Must be the "low mount" or "low profile" type 12 inch to 14 inch mounting height at hook-up point	
c.	Hitch is required to come with all hardware, coupling required to mount the hitch.	

CUTTING EDGE:

a. Must be 1/2 inch by 6 inch by 120 inch high-carbon steel for 10 foot plow and 1/2 inch by 6 inch by 144 inch high-carbon steel for 12 foot plow.

LIFTING DEVICE:.

a. The lifting device shall lift and hold the snow plow in the fully raised position while vehicle is being driven over secondary roads at speeds of 40 mph.

ANGLING DEVICE:

a. Both the 10-foot and the 12-foot plows shall be hydraulically angled minimums of 30 degrees both right and left of center.
b. Maximum plowing angle for both the 10-foot plows (30*) and the 12-foot plows (30*)
c. Clearing path @ maximum angle for both the 10-foot plows (103) and the 12-foot plows (120).

SNOW PLOW MARKERS:

a. Snow plows guide markers shall be provided (high visibility).

15. Addendum